

VEXCEL  
IMAGING

ULTRACAM MERLIN 4.1 2010

## 전문적인 항공 데이터 취득을 위한 관문

---



The UltraCam Merlin 4.1 2010 은 최소한의 비용으로 고품질 항공 영상을 취득할 수 있는 솔루션입니다. 시스템의 촬영 영역은 20,544 x 14,016 픽셀이고, 이는 울트라캠 이글 마크1, 또는 울트라캠 오스프리와 비슷한 수준입니다. Vexcel 의 독보적인 영상 처리

기술을 이용하여 Bayer-pattern 센서로부터 최고의 영상 품질과 기하정확도를 이끌어 냅니다. 또한 Vexcel 의 카메라 하드웨어/소프트웨어 에코시스템의 일원으로 고사양의 제품군으로 업그레이드 옵션을 제공하여 고객의 투자를 보호합니다.

---



# SPECIFICATIONS & DETAILS

## ULTRACAM MERLIN 4.1

2010

True nadir RGB sensor, portrait oriented  
2 x 150 megapixels

True nadir NIR sensor, landscape oriented  
1 x 150 megapixels

SENSOR SYSTEM

Imaging sensor   physical pixel size	CMOS   3.76 µm
Shutter (longlife central leaf)	Prontor magnetic-0 HS2; field exchangeable
Color capability (multi-spectral)	4 channels – RGB Bayer pattern & NIR
Color (RGB Bayer pattern) image size	20,544 x 14,016 pixels
Color (NIR) image size	12,840 x 8,760 pixels
Ratio RGB to NIR	1 : 1.6
Spectral bands (FWHM <sup>1</sup> )	R (580–690 nm) G (480–600 nm) B (420–510 nm) NIR (690–880 nm)

1 frame per 0.7 seconds

Adaptive Motion Compensation

>83 dB at base ISO

14 bits at 4 bands

True Pixel Processing

CAMERA SPECIFICATIONS




Height  
76 cm



Cylinder diameter  
32.5 cm



Power consumption  
230 W (average)  
250 W (peak)



Width  
42 cm



Weight  
44 kg



Operator display  
Vexcel IPT – Interface Panel Touch (2 kg)

LENS SYSTEM



Color (RGB Bayer pattern) lens system focal length	80 mm
Color (RGB Bayer pattern) lens aperture	f=1/4.3
Color (NIR) lens system focal length	50 mm
Color (NIR) lens aperture	f=1/4.2
Total field of view, across track along track	51.5° 36.5°
Footprint for lean restriction of 1 m lean @ 5 m height (across x along)	8,510 x 8,510 pixels




Sample flying heights  
2,128 m @ 10 cm GSD  
1,064 m @ 5 cm GSD

DATA STORAGE

Type  
NVMe solid state disk pack (SSD)

Storage capacity  
16 TB (4x 4 TB)  
32 TB (4x 8 TB)

Size of one raw image (without optional redundancy)  
1,028 MB (771 MB)



Features  
In-flight exchangeable  
Optional redundancy

Number of raw images<sup>2</sup> (without optional redundancy)  
16 TB: up to 14,220 (18,950)  
32 TB: up to 29,660 (39,540)

Weight of data unit  
1 kg

### OPERATIONAL SPECIFICATIONS



FLIGHT ALTITUDE  
≤7,000 m  
above sea level



HUMIDITY  
5% to 95%  
non-condensing



TEMPERATURE  
0 °C to 45 °C  
-20 °C to +45 °C<sup>3</sup> (operation)  
-20 °C to +65 °C (storage)



MOUNTING  
UltraMount and most current third party mounts<sup>4</sup>



GNSS/INS/FMS  
UltraNav and most current third party systems<sup>4</sup>



INSTALLATION  
(Camera, UltraNav & UltraMount)  
≤87 kg  
480 W (average)  
560 W (peak)



DATA PROCESSING  
UltraMap processing suite including data export in standard formats



<sup>1</sup> Full Width at Half Maximum.

<sup>2</sup> Due to configuration and change in SSD technology, usable storage size may vary and can not be guaranteed.

<sup>3</sup> Camera cylinder exposed to outside airflow only.

<sup>4</sup> Please contact our sales team for detailed information.

Technical changes, printing errors and amendments reserved.